

Changelog yuuviz RAD 7.10

Schlüssel	Zusammenfassung	Beschreibung
COOL-15145	You can search for objects with empty table column values	<p>As a user, I want to be able to find those objects that do not have a value in one of the rows for a specific table column, so that I can manually put in the necessary value.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• It is possible to set the 'Without value' / 'Ohne Wert' for a table field in the search dialog• This search finds objects where one of the rows exists with a field without a value.• This search can be saved and reused.• Later: the table shows a set field for 'Without value'
COOL-15242	The REST-WS DmsService.getItem endpoint is able to optionally output null fields as well	<p>As an administrator, I want the rest-ws endpoint DmsService.getItem to optionally output all existing fields of an object, even if the value is null. This applies to the data part, as well as all other parts - baseparameters, contents, versions, etc.. This is necessary if you have to have a static position of the fields in an array or object or if you don't know what fields exist besides the ones with values.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• The null values are written optionally in the case of the DmsService.getItem endpoint.
COOL-15538	The standard process action forward is localized on client-side	<p>As an administrator, I want to be able to localize the standard forward action for the client.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• If the backend does not offer a specific action for a task the client offers a forward button with "Confirm" / "Bestätigen" that can be changed/localized in the language files of the client.
ERA-8126	Catalog value is not changed when changing its localization	<p>As a modeler, I would like to have consistent interface when creating and editing entries in a catalogue or in an object type. Also I would like to have predictable behavior and consistent UI of designer, in order to be able to use it more easily.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• The tree-view of catalogue is based on values, not on neutral-localizations• Localization can occur, same as before, either in properties view, or in dedicated localization view• When creating a new catalog entry, user is offered two fields<ul style="list-style-type: none">• Value• Neutral localization• While in creation state, the value is copied into the neutral localization as long as both entries are identical. Once they diverge (by changing the neutral localization), they are no longer kept in sync and can be edited independently. If they become identical again, they will be kept in sync again.• In the property grid, the value is shown before localization, thus indicating that value is the defining property of a catalogue entry• After creation of an entry has been finished, there is a strict separation between technical values and localization - there is no copying of value into neutral localization
ERA-8163	Process result can be read	<p>As an application developer, I would like to be able to obtain results of a process (the set of configured output parameters), in order to be able use results of a sub-process in the main process.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• The REST interface for getting processes (getProcesses and getProcess) includes an optional response item, result• The requests contain a flag that defines whether to include the process results (where they exist) in response. The flag is set to false by default.• If output parameters are configured for the process, the result is the map that contains the output parameters• If a process does not have output parameters or it is not completed, the result is omitted in REST interface response
ERA-8167	GET /bpm/processes delivers parentProcessId parameter	<p>As client developer, I would like to have necessary information to visualize processes in client that were started as subprocesses, in order that user understands the relation between process instances.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">• GET <hostname>/bpm/processes delivers also the parameter parentProcessId (same as <hostname>/rest-ws/service/bpm/processes does) where available

ERA-8221 Only the configured actions are delivered for a task

As an administrator, I want to be able to localize the standard forward action for the client.

Acceptance criteria:

- The backend delivers only custom actions that have been configured
- If no (custom) action is delivered to the client, the client offers a default forward button with "Confirm" / "Bestätigen"
- This button can be localized in the language files of the client ([GOOL-15538](#))

7 Vorgänge