

Changelog yuvis RAD 6.10

Schlüssel	Komponente (n)	Zusammenfassung	Beschreibung
COOL-12134	yuvis RAD core-service	Meta data extraction is executed during batch object creation	<p>The meta data extraction is not called during batch importing of objects.</p> <p>Acceptance:</p> <ul style="list-style-type: none">The content meta data gets applied to the meta data, if <code>DmsBatchService.createObjects</code> is used.A user is able to prevent the meta data extraction.
COOL-12364	yuvis RAD core-service	The storage and retention dates can be determined while creating the object (createItem)	<p>As with the Batch-createItem, as a developer I would like to be able to specify the storage and retention for the <code>dms.createItem</code>. The aim is to write a document to the archive when it is created.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">The REST endpoint <code>createItem</code> has two new parameters to set the storage and the retention dates.In the REST user interface these parameters can be set as well.
COOL-12377	yuvis RAD core-service	The session handling in core-service is optimized	<p>As a system responsible, I want the system being more stable.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">invalid sessions are removed in all casesit is possible to monitor the active session within the REST-WS interface.<ul style="list-style-type: none">A list of sessions with further information is shownThe amount of open sessions is shownif using JWT-session there is no need to provide cookies
COOL-12410	yuvis RAD search-service	The Search API supports the size of buckets for aggregations	<p>As a programmer, I want to call aggregations with the size of its buckets to fit the users requirements.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">It is possible to use the additional parameter 'size' to define the amount of buckets for an aggregation.It is possible to define the custom default size of aggregation buckets in the yaml-file. Default is 20.
COOL-12411	yuvis RAD client	The editing of form tables is optimized	<p>As a user, I want to be supported by some smaller optimizations while editing table data as described in the criteria below.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">There is an 'x' in the form area to close the form.In the form title a hint is given if the user is working on a new row.After saving form data as a new row this new row is highlighted for a short whileIn case of many rows the list scrolls to the end after saving a new row.After click onto 'remove' a security question is offered with 'OK' and 'Cancel'. The focus is on 'OK'.The icons in the table header are looking more similar.There are buttons with words instead of symbols for saving.In case of a new row there is a checkbox 'Insert new row'. If checked the form for inserting a new row is opened again after save to enter the next one.
COOL-12416	yuvis RAD client	You can configure the browser tab name of the dashboard	<p>As a system integrator, I want to be able to configure the component name that is shown in the browser-tab of the dashboard concerning an OEM setting.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none">The component name that is shown in the browser-tab of the dashboard can be configured in the client config file.To be discussed: name in the help state

COOL-12422	yuuviv RAD agent	The agent API offers an information whether a user is allowed to save an object in the general filing location	<p>As a programmer, I want to be able to request via agent whether the logged-in user is allowed to save an object in the general filing location so that I can offer this function within my application using the agent API.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none"> • GetConnection() and GetLocationsAndFavorites() can be called in a way that returns the information <ul style="list-style-type: none"> • whether the general filing location can be offered for creating a new object or not • and whether it is allowed to create a template object (capability for this feature is active)
COOL-12470	yuuviv RAD client	The customization of client settings is optimized	<p>As an administrator, I want to change the client configurations in a way that updates don't overwrite my changes and that new client keys are affected as well.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none"> • Instead of changing the settings in ...service-manager\data\webresource\public\client\assets_default\config\main.json the settings have to be changed in a file ...service-manager\data\webresource\resources\client\assets_default\config. This file only contains the changed values. All other values are read from the standard file.
COOL-12484	yuuviv RAD core-service, yuuviv RAD management-studio	You can empty the recycle bin	<p>As an administrator, I want to be able to empty the recycle bin of a user.</p> <p>Current solution: select <u>one</u> object and call an action.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none"> • There is an operation that allows to empty the recycle bins: <ul style="list-style-type: none"> • It is possible to configure the days an object has been in the recycle bin. In case of '0' all objects are deleted. • It is possible to configure a list of users. The corresponding bins are deleted. If no user is configured all bins are deleted.
ERA-7362	yuuviv RAD core-service	All yuuviv RAD locks can be removed via REST interface	<p>As an administrator, I would like to be able to remove all existing locks at once in case that something went wrong and that locks remained although they should have been removed.</p> <p>Acceptance criteria:</p> <ul style="list-style-type: none"> • There is an internal REST endpoint to manually remove all locks that were placed on schema, security and organisation. • This removal can be done also from another server-node. • Endpoint is documented and available in our rest-ws

10 Vorgänge